

DisplayPort to HDMI Adapter - 1080p Compact DP to HDMI Adapter/Video Converter - VESA DisplayPort Certified - Passive DP 1.2 to HDMI Monitor/Display/Projector Cable Adapter

Product ID: DP2HDMIADAP



The DP2HDMIADAP DisplayPort to HDMI Adapter provides a DisplayPort male and HDMI female connector, allowing you to keep your existing (HDMI) display while using a DisplayPort video card/source.

Supporting display resolutions of up to 1920x1200 (computer)/1080p (HDTV), this cost-effective solution maintains the incredible graphical performance offered by DisplayPort, while eliminating the cost of having to upgrade your HDMI-capable display to a display with built-in DisplayPort support.

DP2HDMIADAP is a passive adapter cable that requires a DP++ port (DisplayPort++), meaning that DVI and HDMI signals can also be passed through the port.

This adapter allows for audio pass-through if supported by the video source. Please review the video source manual to confirm support.

Backed by a StarTech.com 3-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility

Applications

• The DisplayPort to HDMI adapter allows for an easy and hassle free connection to any HDMI-enabled display

Features

• PERFORMANCE: This DisplayPort 1.2 to HDMI adapter connects a DP desktop or laptop to an HDMI display, projector, monitor or TV Supports HD 1920x1200 (1080p) video, 7.1ch Audio, HDCP 1.4 VESA DisplayPort Certified



• HOST COMPATIBILITY: DisplayPort to HDMI adapter tested for compatibility with DP++ source; Passive converter supports DP++ source connector incl workstations, desktops (AMD/Nvidia video cards), laptops, small form factor computers & docking stations

• SMALL FORM FACTOR: With no attached cable and compact design, the adapter connects directly to your HDMI cable for a clean look Use to connect primary monitor or projector or add a secondary display Perfect for travel and easily fits into a bag pocket

• STABLE CONNECTION: DP to HDMI adapter features a non-latching DP connector that is easy to disconnect from a hard to reach source Tested with HDMI cables at extended lengths up to 35ft

• EASY TO USE: With no software or drivers required, the DisplayPort to HDMI video adapter is OS independent; DP male to HDMI female

Warranty 3 Years Active or Passive Adapter Passive AV Input DisplayPort - 1.2 AV Output HDMI Audio Yes Performance Maximum Cable Distance resolutions 49.9 ft [15.2 m] 1920x1200 / 1080p Maximum Digital Resolutions 1920x1200 / 1080p Audio Specifications HDMI - 7.1 Channel Audio Connector A DisplayPort (20 pin) Connector B HDMI (19 pin) Special Notes / Requirements DP++ port (DisplayPort ++) required on video card or video source (DVI and HDMI pass-through must be supported)			
Active or Passive Adapter Passive AV Input DisplayPort - 1.2 AV Output HDMI Audio Yes Performance Maximum Cable Distance 49.9 ft [15.2 m] Maximum Digital 1920x1200 / 1080p Resolutions HDMI - 7.1 Channel Audio Connector (A) DisplayPort (20 pin) Connector B HDMI (19 pin) Special Notes / Requirements System and Cable Puriormantel DisplayPort (20 pin) Connector B DP++ port (DisplayPort ++) required on video card or video source (DV1 and HDMI pass-through must be supported)	Hardware		
AV Input DisplayPort - 1.2 AV Output HDMI Audio Yes Performance Maximum Cable Distance 49.9 ft [15.2 m] Maximum Digital 1920x1200 / 1080p Resolutions HDMI - 7.1 Channel Audio Connector A DisplayPort (20 pin) Connector B HDMI (19 pin) Special Notes / System and Cable Environmental Operating Temperature Special Notes / Sc to 35C (41F to 95F)		Warranty	3 Years
AV Output HDMI Audio Yes Performance Maximum Cable Distance 49.9 ft [15.2 m] To Display 1920x1200 / 1080p Maximum Digital 1920x1200 / 1080p Resolutions HDMI - 7.1 Channel Audio Connector(s) Connector A DisplayPort (20 pin) Connector B HDMI (19 pin) Special Notes / Requirements System and Cable DP++ port (DisplayPort ++) required on video card or video source (DVI and HDMI pass-through must be supported) Environmental Operating Temperature 5C to 35C (41F to 95F)		Active or Passive Adapter	Passive
AudioYesPerformanceMaximum Cable Distance To Display9.9 ft [15.2 m] 1920x1200 / 1080p Audio SpecificationsMaximum Digital Resolutions1920x1200 / 1080p HDMI - 7.1 Channel AudioConnector (s) Connector ADisplayPort (20 pin) EnvironmentalSpecial Notes / RequirementsSystem and Cable RequirementsDP++ port (DisplayPort ++) required on video card or video source CV1 and HDMI pass-through must be supported)EnvironmentalOperating TemperatureSc to 3SC (41F to 9SF)		AV Input	DisplayPort - 1.2
Performance Maximum Cable Distance 49.9 ft [15.2 m] To Display Maximum Digital Resolutions 1920x1200 / 1080p Audio Specifications HDMI - 7.1 Channel Audio Connector(s) Connector A DisplayPort (20 pin) Connector B HDMI (19 pin) Special Notes / Requirements System and Cable Requirements DP++ port (DisplayPort ++) required on video card or video source (DVI and HDMI pass-through must be supported) Environmental Operating Temperature 5C to 35C (41F to 95F)		AV Output	HDMI
Maximum Cable Distance 49.9 ft [15.2 m] To Display 1920x1200 / 1080p Resolutions HDMI - 7.1 Channel Audio Connector(s) Connector A DisplayPort (20 pin) Connector B HDMI (19 pin) Special Notes / Requirements System and Cable Requirements DP++ port (DisplayPort ++) required on video card or video source (DVI and HDMI pass-through must be supported) Environmental Operating Temperature 5C to 35C (41F to 95F)		Audio	Yes
To Display To Display Maximum Digital Resolutions 1920x1200 / 1080p Audio Specifications HDMI - 7.1 Channel Audio Connector(s) Connector A DisplayPort (20 pin) Connector B HDMI (19 pin) Special Notes / Requirements System and Cable Requirements DP++ port (DisplayPort ++) required on video card or video source (DVI and HDMI pass-through must be supported) Environmental Operating Temperature 5C to 35C (41F to 95F)	Performance		
Resolutions Audio Specifications HDMI - 7.1 Channel Audio Connector(s) Connector A DisplayPort (20 pin) Connector B HDMI (19 pin) Special Notes / Requirements System and Cable Requirements DP++ port (DisplayPort ++) required on video card or video source (DVI and HDMI pass-through must be supported) Environmental Operating Temperature 5C to 35C (41F to 95F)			49.9 ft [15.2 m]
Connector(s) Connector A DisplayPort (20 pin) Connector B HDMI (19 pin) Special Notes / Requirements System and Cable Requirements DP++ port (DisplayPort ++) required on video card or video source (DVI and HDMI pass-through must be supported) Environmental Operating Temperature 5C to 35C (41F to 95F)			1920x1200 / 1080p
Connector A DisplayPort (20 pin) Connector B HDMI (19 pin) Special Notes / Requirements System and Cable Requirements DP++ port (DisplayPort ++) required on video card or video source (DVI and HDMI pass-through must be supported) Environmental Operating Temperature 5C to 35C (41F to 95F)		Audio Specifications	HDMI - 7.1 Channel Audio
Connector B HDMI (19 pin) Special Notes / Requirements System and Cable Requirements DP++ port (DisplayPort ++) required on video card or video source (DVI and HDMI pass-through must be supported) Environmental Operating Temperature 5C to 35C (41F to 95F)	Connector(s)		
Special Notes / Requirements System and Cable Requirements DP++ port (DisplayPort ++) required on video card or video source (DVI and HDMI pass-through must be supported) Environmental Operating Temperature 5C to 35C (41F to 95F)		Connector A	DisplayPort (20 pin)
Requirements System and Cable Requirements DP++ port (DisplayPort ++) required on video card or video source (DVI and HDMI pass-through must be supported) Environmental Operating Temperature 5C to 35C (41F to 95F)		Connector B	HDMI (19 pin)
Requirements (DVI and HDMI pass-through must be supported) Environmental Operating Temperature 5C to 35C (41F to 95F)	Special Notes / Requirements		
Operating Temperature 5C to 35C (41F to 95F)			
	Environmental		
Storage Temperature -20C to 60C (-4F to 140F)		Operating Temperature	5C to 35C (41F to 95F)
		Storage Temperature	-20C to 60C (-4F to 140F)



	Humidity	65% 10%RH
Physical Characteristics		
	Color	Black
	Product Length	2.2 in [55 mm]
	Product Width	0.7 in [18 mm]
	Product Height	0.4 in [9 mm]
	Weight of Product	0.6 oz [16 g]
Packaging Information		
	Package Length	4.9 in [12.5 cm]
	Package Width	3.5 in [90 mm]
	Package Height	0.4 in [11 mm]
	Shipping (Package) Weight	0.6 oz [18 g]
What's in the Box		
	Included in Package	DisplayPort to HDMI Adapter

*Product appearance and specifications are subject to change without notice.

