

# ACRYLIC BONDING AND PRIMING AGENT

## ADHESION PROMOTER FOR WALLS AND FLOORS



### DESCRIPTION:

Acrylic Bonding and Priming Agent is a blue pigmented opaque liquid for use in promoting adhesion and reducing porosity of a variety of surfaces. The presence of the blue colour indicates that the product has been applied according to recommendations and helps to ensure an even continuous coating has been applied.

### PREPARATION:

Ensure surface to be treated is completely dry.

### APPLICATION:

Apply using a brush or roller at the recommended strength and allow to dry before tiling. The product is water based and will dry in approx. 1 hour in good drying conditions.

#### Plaster

Apply Granfix Acrylic Bonding and Priming Agent diluted 3 parts water to 1 part bonding agent to seal plaster before applying ready mixed acrylic paste. Apply 2 neat coats of Granfix Acrylic Bonding and Priming Agent to plaster before applying any cementitious adhesive.

#### Concrete, renders, brickwork, blockwork, plasterboard, cement board

Apply Acrylic Bonding and Priming Agent diluted 3 parts water to 1 part bonding agent to these surfaces as a primer and sealer. Reduces suction and therefore improves adhesion and application of adhesive on dry porous surfaces. Will prevent dusting on concrete floors. Coverage: 40 square metres per litre diluted\*<sup>1</sup>

#### Timber surfaces, vinyl, asphalt, anhydrite screeds

Apply Acrylic Bonding and Priming Agent (as instructed on the relevant adhesive data sheets) to these surfaces to promote adhesion, improve application and coverage of adhesive. Coverage: 10 square metres per litre\*<sup>2</sup>

### FLOOR MAINTENANCE:

The floor should be maintained with Granfix EasiCare products.

**PACK SIZES:** 1 Litre, 2.5 Litre and 5 Litre.

**COLOUR:** Blue Opaque Liquid.

**COVERAGE:** 40metre<sup>2</sup> per Litre when diluted \*<sup>1</sup>  
10metre<sup>2</sup> per Litre neat \*<sup>2</sup>

**STORAGE:** Store unopened in cool dry conditions. Protect from frost.

**SHELF LIFE:** Stored correctly, this product has a shelf life of 12 months from the date shown on the packaging.

### TECHNICAL DATA:

Specific Gravity: 1Kg per Litre

Application temperature: Between 5°C and 30°C

Service Conditions: -20°C to +50°C

Drying Time: 1 hour

\*Note: All times refer to site conditions of 20°C. These times will be increased at lower temperatures and reduced at elevated temperatures.

The information given on this technical sheet is accurate and given in good faith. However, it is given without guarantee as conditions of use and workmanship are beyond the control of Granfix Products. All information is subject to the company's terms and conditions of sale, copies of which are available on request.