

WETROOM SYSTEM READY MIXED

READY TO USE FLEXIBLE WATERPROOF COATING FOR PROTECTION OF WATER SENSITIVE BACKGROUNDS IN WET ROOMS



DESCRIPTION:

Black pigmented solvent free soft paste which dries to give a flexible waterproof coating for protection of water sensitive backgrounds prior to tiling.

Suitable for situations such as domestic kitchens, bathrooms, showers and commercial applications. This product is suitable for use in internal locations where water will drain from the floor surface with a slight fall.

Unsuitable for swimming pools or where there is continuous water immersion.

PREPARATION:

Before commencing, all surfaces must be clean, dry, firm and free from movement. Remove all loose dust, dirt, oil, grease, etc and other contaminants likely to affect adhesion.

METHOD OF USE:

Apply using a brush or short pile roller to give a continuous thin layer of product at least 0.4mm thick.

Junctions between wall and floor and all corners should be reinforced with Granfix mesh scrim and any other places where movement cracking could occur.

Allow to dry for approx 2 hours before applying a second coat. This time will be extended depending on thickness applied, porosity of background and temperature if less than 20°C.

The floor should be dry enough for walking on without damage. Allow to dry for 24 hours before foot traffic or commencing tiling.

TILE FIXING:

Should be carried out using a Polymer Modified Cement Based Adhesive such as 1 Part Rapidset, Porcelainfix, Marblefix etc. Ready Mixed Adhesive is NOT recommended. Apply 1 coat neat of Granfix Acrylic Bonding and Priming Agent to Wetroom System prior to tiling.

APPLICATIONS:

New Brickwork, Blockwork and Concrete: Must be fully cured and dry prior to tiling. Surface must be reasonably flat.

Gypsum Plaster/Anhydrite Type Floors: Must be completely dry. Apply 1 coat of Granfix Acrylic Bonding and Priming Agent neat prior to application of Wetroom System.

Timber Walls/Floors: Background must be clean and free from any loose matter and the surface must be sound, dry and flat. Boards should be firmly fixed to supporting joists and free from any excessive or sudden movement. For floorboards, overlay with 15mm exterior grade plywood screw fixed at 150mm centres.

Note: Moisture sensitive backgrounds should be protected from moisture ingress from behind.

PACK SIZES: 8Kg

COLOUR: Dark Grey

COVERAGE: Ceramic Tiles - 0.5Kg per metre²

STORAGE: Store unopened in cool dry conditions. Protect from frost.

SHELF LIFE: Stored correctly, this product has a shelf life of 12 months from the date shown on the packaging.

TECHNICAL DATA:

Paste Density:	1.1Kg per Litre
Application temperature:	Between 5°C and 30°C
Service Conditions:	-20°C to +50°C
First Coat Drying:	2 hours*
Second Coat Drying:	2 hours*
Before Tiling:	24 hours*
Contact with Water:	7 Days

*Note: All times refer to site conditions of 20°C. These times will be increased at lower temperatures and reduced at elevated temperatures.

The information given on this technical sheet is accurate and given in good faith. However, it is given without guarantee as conditions of use and workmanship are beyond the control of Granfix Products. All information is subject to the company's terms and conditions of sale, copies of which are available on request.