

GRANFIX

PRODUCTS

An **INSTARMAC** Brand

TILE ADHESIVES | GROUTS
ANCILLARY PRODUCTS

TECHNICAL DATA SHEET

ACRYLIC BONDING & PRIMING AGENT

Enhances adhesion to Wood, Asphalt
and Concrete
Seals Floors



Easy to Use



Promotes Adhesion



Reduces porosity

1L & 5L

ACRYLIC BONDING & PRIMING AGENT

Enhances adhesion to Wood, Asphalt and Concrete Seals Floors

Imparts excellent adhesion to concrete, timber, plaster, adhesive residues, existing tiles, vinyl tiles and a variety of substrates. Can be used where damp conditions are likely to be encountered, but NOT suitable for areas where rising damp is present.

SURFACE PREPARATION

All surfaces must be dry and free from any plaster dust, dirt, oil, grease, wax, debris and other contaminants likely to affect adhesion. Smooth or shiny surfaces, such as glazed tiles, should be abraded first to provide a mechanical key.

CONCRETE AND OTHER POROUS SURFACES

Apply 1 coat of GRANFIX ACRYLIC BONDING & PRIMING AGENT diluted to 3 parts water to 1 part bonding agent as a primer and sealer.

PLASTER

Apply 1 coat of GRANFIX ACRYLIC BONDING & PRIMING AGENT diluted to 3 parts water to 1 part bonding agent plaster before applying ready mixed acrylic paste. Apply 2 neat coats of GRANFIX ACRYLIC BONDING & PRIMING AGENT to plaster before applying any cementitious adhesive.

TIMBER

Apply 1 coat of GRANFIX ACRYLIC BONDING & PRIMING AGENT diluted to 1 part water to 1 part bonding agent.

ADHESIVE RESIDUES, ASPHALT, FLOOR TILES AND VINYL TILES

Mix 1 part by weight of GRANFIX ACRYLIC BONDING & PRIMING AGENT with 1 part Portland Cement to form a slurry. Apply to surface. Allow to dry. Takes approx 1 hour.

OTHER APPLICATIONS

Refer to product information on the adhesive packaging.

PACK SIZES

1L and 5L

STORAGE

Store in airtight containers between 5°C and 30°C. Protect from frost and direct sunlight.

SHELF LIFE

12 months in the above conditions.

HEALTH, SAFETY AND ENVIRONMENTAL

Please ensure that appropriate PPE is used when preparing, mixing and applying products. Always wash hands before consuming food and make sure that materials are kept safely out of reach of children and animals. Please dispose of packaging and waste responsibly and in accordance with local authority requirements. A full material safety data sheet relating to this product is available from tileadhesive.co.uk.

QUALITY ASSURANCE

All products are manufactured in a plant whose quality management system is certified / registered as being in conformity with BS EN ISO 9001, ISO 14001 and OHSAS 18001. Our products are guaranteed against defective materials and manufacture and will be replaced or money refunded if the goods do not comply with our promotional literature. We cannot however accept responsibility arising from the application or use of our products because we have no direct or continuous control over where and how projects are used. All products are sold subject to our conditions of sales, copies of which may be obtained upon request.

Vers I.12.2015 Information correct at time of print.



INSTARMAC GROUP PLC
DANNY MORSON WAY • BIRCH COPPICE BUSINESS PARK
DORDON • TAMWORTH • STAFFORDSHIRE • B78 1SE

TEL: +44 (0)1827 872244 • FAX: +44 (0)1827 874466
ENQUIRIES: email@instarmac.co.uk
ORDERS: orders@instarmac.co.uk

www.tileadhesive.co.uk