

GRANFIX

PRODUCTS

An **INSTARMAC** Brand

TILE ADHESIVES | GROUTS
ANCILLARY PRODUCTS

TECHNICAL DATA SHEET

MAXIGROUT XTRA

Fast Setting Wall & Floor Grout

For Grouting Internal and External Tiles

Available in White, Ivory, Bahama Beige, Jasmine, Limestone,
Silver, Grey, Charcoal, Brown and Black



Easy to Use



Underfloor Heating
Compatible



Conforms to:
BS EN 13888 CG2



Suitable For Kitchens
& Bathrooms



Flexible
Polymer Modified



Mould Resistant



For Joints of
1mm-20mm



Water Resistant
For Showers & Swimming Pools

3Kg & 10Kg

MAXIGROUT XTRA

Fast Setting Wall & Floor Grout

MAXIGROUT XTRA has been specially designed for areas where movement or vibration is likely. With excellent joint filling capacity, the product allows for joints up to 20mm to be filled in one application. Polymer has been added to the formulation to increase flexibility and to provide a virtually impermeable set. MAXIGROUT XTRA grout is suitable for use with most common tile applications including natural stone, porcelain, conglomerate and ceramic wall and floor tiles.

PRECAUTION

Certain tiles may suffer from discoloration or scratching when using grouts. We would recommend that a test application be carried out prior to grouting. Our grouts go through stringent checks to ensure quality and colour, however due to the use of raw materials we suggest a trial area to ensure colour is consistent and as expected.

SURFACE PREPARATION

Ensure that the adhesive is completely set and that the tiles are firmly fixed. Ensure that joints are free from excess adhesive, dust, grease or any other contaminants.

MIXING

MAXIGROUT XTRA grout powder should be added slowly to clean water in a suitable container in the appropriate proportion of 2.75 parts powder to 1 part water for White and Ivory. 3.25 parts powder to 1 part water for Jasmine and Silver. 3.5 parts powder to 1 part water for Limestone, Grey, Charcoal, Brown and Black. Mix until a smooth consistency is achieved, leave to stand for 2 minutes then remix. Do not mix more than can be used in a 45-60 minute period, do not re-wet or add too much water.

APPLICATION

MAXIGROUT XTRA grout should be applied to the surface using a rubber backed trowel or squeegee. Work the mixed material thoroughly into the joints, a small area at a time. Ensure that the joints are completely filled without voids before continuing. Excess grout should be removed as grouting proceeds. Any residue left on the face of the tile can be removed by wiping with a damp sponge when the grout has started to firm (approximately 15 mins - when using a normal ceramic tile. On non-absorbent tiles such as porcelain, this may take up to an hour). Any dry film remaining once the job is complete can be polished off the face of the tiles with a soft dry cloth. Finishing when the grout is not firm to the touch, may lead to joints being emptied or potential colour variation.

HEALTH, SAFETY AND ENVIRONMENTAL

Please ensure that appropriate PPE is used when preparing, mixing and applying products. Always wash hands before consuming food and make sure that materials are kept safely out of reach of children and animals. Please dispose of packaging and waste responsibly and in accordance with local authority requirements. A full material safety data sheet relating to this product is available from tileadhesive.co.uk.

QUALITY ASSURANCE

All products are manufactured in a plant whose quality management system is certified / registered as being in conformity with BS EN ISO 9001, ISO 14001 and OHSAS 18001. Our products are guaranteed against defective materials and manufacture and will be replaced or money refunded if the goods do not comply with our promotional literature. We cannot however accept responsibility arising from the application or use of our products because we have no direct or continuous control over where and how projects are used. All products are sold subject to our conditions of sales, copies of which may be obtained upon request.

TECHNICAL DATA

Packaging:	3kg & 10kg bags
Standard	
Compliance:	CG2, EN13888
Initial Drying Time:	10-15min*
Pot Life:	30-60min*
Set Time:	Within 24 hours*
Application Thickness:	1mm-20mm
Protein Free:	Yes

*The above technical data is dependent on colour and temperature.

Storage:	This product must be stored clear of the ground in cool, dry conditions and protected from excessive drafts.
Shelf Life:	Unopened bags 12 months in cool, dry conditions above 5°C and below 30°C. Avoid frost.

Vers2.02.2017 Information correct at time of print.

www.tileadhesive.co.uk

GRANFIX
PRODUCTS

INSTARMAC GROUP PLC
DANNY MORSON WAY • BIRCH COPPICE BUSINESS PARK
DORDON • TAMWORTH • STAFFORDSHIRE • B78 1SE

TEL: +44 (0)1827 872244 • FAX: +44 (0)1827 874466
ENQUIRIES: email@instarmac.co.uk
ORDERS: orders@instarmac.co.uk