TECHNICAL DATA SHEET

SG05 Mono Basin Mixer (Inc. Sprung Waste)

Barcode Product Code Construction Finishes Product Type Water Pressure Plumbing Systems Standards Certification Cartridge Fitting

Packaging Guarantee Additional Information 729557183218 SG05 Brass Body CuZn40Pb2, EN CW617N (equivalent to BS CZ122) Chrome plated to BS EN 248 Contemporary Min. 0.2 bar, Max. 6.0 bar Suitable for all plumbing systems Complies with BS6920, BS EN200 Manufactured to comply with WRAS 35mm ceramic disc cartridge UK: M10 x 350mm ½" BSP Female Flexi Tails . EU: M10x350mm 3/8" BSP Female Flexi Tails . S5.5 x 27 x 42cm / carton (10 boxes / carton) 10 years against manufacturing faults (excluding serviceable parts). Supplied with G 1¼" sprung waste(UK only), Air Aerator

Flow Rates (Litres per minute)

System Pressure	0.1 Bar	0.2 Bar	0.3 Bar	0.5 Bar	1.0 Bar	1.5 Bar	2.0 Bar	3.0 Bar	4.0 Bar	5.0 Bar
SG05	3.20	3.80		5.30	6.80	8.20	9.50	11.30	-	-

The information contained on this page was correct at date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. We pursue a policy of continuing improvement in design and performance of our products and so reserve the right to change specifications without prior notice.

